



FF1000

➔ Time Attendance and Access Control System

Face Capacity : 1,000
 Card Storage : 2,000 (Optional)
 Transaction storage : 1,00,000
 Card reader : Yes
 Fingerprint sensor : NA
 FAR : $\leq 0.0001\%$
 FRR : $\leq 1\%$
 Identification speed : ≤ 1 sec
 Display : 2.8" TFT Screen
 Keypad : 4 x 4 Function Keys
 LED Indicator : Green/Red
 Schedule Bell/Speaker : Mini Speaker
 Communication : RS232/RS485/TCP IP USB Host
 Push data : NA
 Standard features : Work Code, SMS, DST,
 Scheduled bell, Self Service Query,
 Automatic Status Switch, Photo ID, Camera,
 9 Digit User, Multiple Verify Mode, External bell

Power Supply : DC 12V, 3A
 operating temperature : 0°C-45°C
 Operating Humidity : 20%-80%
 Dimension : 173 X 159 X 36.1 mm
 Weight : 475 gm
 Access control : Wiegand : Output
 Support Fire Alarm : Yes
 Door Sensor : Yes | Anti Passback : No
 Door Bell : Yes
Optional :
 Battery : Built-in Battery
 Card readers : ID/Mifare
 Communication : No
 Dual Mode : No