

uFace 602



➔ Multi-Biometric T&A and Access Control System

Face capacity : 1,200 (3000 Optional) 1:N
Fingerprints templates : 2000
Card Storage : 10,000 (optional)
Transaction storage : 1,00,000
Card reader : Yes
CPU : 1.0GHz
Fingerprint sensor : 500 DPI Optical sensor
FAR : $\leq 0.0001\%$
FRR : $\leq 1\%$
Identification speed : < 0.5 sec
Algorithm Ver : 10
Display : 4.3-Inch Touch Screen
Keypad : 4 x 4 with 5 function Keys
LED Indicator : Green/Red
Schedule Bell/Speaker : Mini Speaker
Communication : TCP/IP, RS232/485, USB Host
Push data : Yes
Power Supply : 12V 3A
Operating Temperature : 0 °C - 45 °C
Operating Humidity : 20% - 80%
Dimension : 194.1x169x109.0mm
Wiegand : Output

Relay : 12 V relay for lock EM lock, Bolt Lock or Strike lock

Support Fire Alarm : Yes

Door Sensor : Yes

Anti Passback : Yes

Door Bell : Yes

Support exit readers : No

Battery : 7.4 V, 2000 mAh Backup Battery

Compatible :

- Compatible with Multi Door controllers via weigand
- External Speaker output available (Optional)
- External Bulb output available (Optional)
- Support External Printer

Compatible Software and SDK:

- Smart office suite desktop and web
- etime track lite desktop & web
- SDK for desktop applications
- Web based Device Manager/ePush server using Push data.

Helps developers & integrators

- Supports 3rd Party Payroll/HRMS/ERP and Other applications