

K200



➔ Proximity Time and Attendance System

Card Capacity : 30,000
 Transaction Storage : 50,000
 CPU : 32 bit microprocessor
 Read Range : 8-10 cms
 FAR : $\leq 0.0001\%$ / FRR : $\leq 1\%$
 Identification Speed : ≤ 0.5 sec
 Algorithm Ver : 10
 Display : 128 x 64 OIED with white Color
 Keypad : 4 x 4 Keypad
 LED Indicator : Green/Red
 Schedule Bell/Speaker : Mini Speaker
 Communication : RS232/485, TCP/IP
 Camera : High Resolution Infrared Camera
 Standard Features : DLST, Automatic Status Switch
 Status Switch, Workcode, T9 Input
 Power Supply : 5V DC, 400mA
 Operating Temperature : 0°C to 45°C
 Operating Humidity : 20% -80%
 Dimension : 90 x 190 x 3.5 mm

Access Control:

Wiegand : In-Out both 26 or 34 bit
 (With or without site code)
 Relay : 12 V / Support Fire Alarm: Yes
 Door Sensor : Yes / Anti Passback : Yes
 Door Bell : Yes / Battery : Yes

Compatibility :

- External Speaker output available (Optional)
- External Bulb output available (Optional)
- 3rd party electric lock, Door sensor, Exit button

Compatible Software & SDK :

- Smart office suite desktop and web
- Etime track lite desktop & web
- SDK for desktop applications
- Web based Device Manager/ePush server using Push data. Helps developers & integrators
- Supports 3rd Party Payroll/HRMS/ERP & Other applications