



## Multibio 700

### ➔ Multi-biometric Identification Time Attendance & Access Control System

Fingerprint Templates : 2000  
Face Capacity : 1500  
Card Capacity : 10,000  
Transaction storage : 1,00,000  
Card Reader : Yes  
Image Sensor : Special Sterio Dual Sensor  
FAR :  $\leq 0.0001\%$  / FRR :  $\leq 1\%$   
Identification Speed :  $\leq 1$ Sec  
Algorithm Ver : 10  
Display : 3" Touch Screen  
Keypad : 2 Function Keys  
Schedule Bell/Speaker : Mini Speaker  
Communication : RS232/485, TCP/IP,  
USB-Host  
Camera : High Resolution Infrared Camera  
Standard Features : ID Card, Automatic Status  
Switch, Self Service Query Work code  
Power Supply : 12V DC, 1.5 Amps  
Operating Temperature : 0°C to 45°C  
Operating Humidity : 20% -80%  
Dimension : 195 x 100 x 275 mm

#### Access Control :

Wiegand : Both 26 & 32 Bit In and Out  
Relay : 12 V  
Support Fire Alarm : Yes / Door Sensor ; Yes  
Anti Passback : No / Door Bell : Yes  
Support exit reader : KR 500, 101 HE  
Battery : No / Card Readers : Yes  
Communication : No  
Printer : No

#### Compatibility :

- 3rd party electric lock, Door sensor, Exit button

#### Compatible Software & SDK :

- Smart office suite desktop and web  
- Etime track lite desktop & web  
- SDK for desktop applications  
- Web based Device Manager/ePush server using  
Push data. Helps developers & integrators  
- Supports 3rd Party Payroll/HRMS/ERP  
and Other applications