



Bi-direction type - TS1200 series:

TS1200	TS1211	TS1222
Tripod Turnstile	RFID	FP + RFID

➔ TS1200 - Twoway vertical Tripod turnstile

Type : Vertical Tripod

Arm Length : 50cm

Max tolerance of Arms : 80 Kg

Angle per rotation : 120°

Operation Type : Twoway - Bidirectional

Flow Rate : 25-48 passages/minute

Input control signal : Dry contact

Ingress protection Degree : IP54

Opening Duration : 5s - 60s

Hardware & Interface :

Primary controller (Inbuilt)

CPU : 32 bit Microprocessor

Opening Signal Input : yes

Emergency Switch Input : yes

Direction Indicator Output : yes

Passing Indicator Output : Yes

Drop Arm Electromagnet Output : Yes

Optional Interface :

Any Standalone access controller system
Eg. X990, IFACE, SC403, X7, SF101, F702 etc.

Power Supply :

SMPS - Input : AC 220V / 110V, 50Hz / 60Hz

SMPS - output : DC +24V, 5A; +12V, 3A

Dimension(mm) : L = 520, W = 280, H = 980

Gross Weight : 63kg

Operating Temperature : -28°C to +60°C

Operating Humidity : 5% - 85%

Operating Environment : Indoor & Outdoor(shelter)

Dimension : (All units in mm)

