

HC-IPC-D4211-0360

- › Day/night functionality
- › Optical glass window with higher light transmittance
- › IR anti-reflection window to increase the infrared transmittance
- › Up to 30 m (98 ft) IR distance
- › 3D noise reduction
- › H.264/MJPEG
- › Triple streams
- › ONVIF Conformance
- › Support PoE power supply (optional)
- › Wide temperature range: -35°C to 60°C (-31°F to 140°F)
- › Wide voltage range of ±25%
- › 4 KV surge protection designed for network interface
- › IP66

SPECIFICATION



Sensor	1/3", 1.3 megapixel, progressive scan, CMOS
Lens	3.6mm@F1.8, Angle of view(H)76.7°
Shutter	Auto/Manual, 1/6~1/30,000 s
Min. Illumination	Colour: 0.02 Lux (F2.0, AGC ON), 0 Lux with IR
Day/Night	IR-cut filter with auto switch (ICR)
IR	30m (98 ft) IR range
AWB(Auto white balance)	Auto/manual
Gain Control	Auto/manual
WDR	Digital
Noise Reduction	2D/3D
Max. Resolution	1280×960
Video Compression	H.264/MJPEG
Frame Rate	960P (1280×960): Max. 30 fps; 720P (1280×720): Max. 30 fps; D1 (720×576): Max.25fps
Video Streaming	Triple
OSD	Up to 8 OSDs
Motion Detection	Up to 2 areas
Privacy Mask	Up to 4 areas
Protocols	IPv4,IGMP,ICMP,ARP,TCP,UDP,DHCP,RTP,RTSP,Qos,DNS,DDNS,NTP,FTP,UPnP,HTTP
Compatible Integration	ONVIF
Network	10M/100M Base-TX Ethernet



SPECIFICATION



Power	12 V DC, or PoE (IEEE802.3 af) Power consumption: 3.5 W (5.5W with IR on)
Dimensions (Ø x H)	Ø126 x 94 mm (Ø5.0" x 3.7")
Weight	0.33 kg (0.73 lb)
Working Environment	-35°C ~ +60°C (-31°F ~ 140°F), Humidity ≤ 90% RH(non-condensing)
Ingress Protection	IP66

