

HC-IPC-D4213D-VF

- › Day/night functionality
- › Smart IR , up to 30 m (98 ft) IR distance
- › Lowlight surveillance
- › 3D DNR (Digital Noise Reduction)
- › H.264 High Profile
- › Triple streams
- › ROI (Region of Interest)
- › 9:16 corridor mode
- › ONVIF Conformance
- › Support PoE power supply
- › Built-in PoE splitter that outputs DC 12V
- › Wide temperature range: -40°C to 60°C (-40°F to 140°F)
- › Wide voltage range of ±25%
- › IK10 vandal resistant
- › IP66
- › 6KV Surge



SPECIFICATION



Sensor	1/2.8", 3 megapixel, progressive scan CMOS
Lens	2.8~12 mm@F1.4; Angle of View (H): 100.0° (wide) ~30° (tele)
Shutter	Auto/Manual, 1/6~1/8000 s
Min. Illumination	Colour: 0.03 Lux (F1.4, 50IRE) / Black & White: 0.01Lux (F1.4, 50IRE)
Zoom/Focus	Manual
Day/Night	IR-cut filter with auto switch (ICR)
IR Range	Up to 30m (98 ft) IR range
S/N	>52dB
WDR	Optical WDR(up to 120dB)
Edge Storage	Micro SD, up to 128 GB
Max. Resolution	2048 × 1536
Video Compression	H.264/MJPEG
Frame Rate	3MP(2048x1536) Max.25fps; 1080P (1920x1080): Max. 30 fps; 720P (1280x720): Max. 30 fps; D1 (720x576): Max. 25 fps
9:16 Corridor Mode	Supported
ROI	Supported
OSD	Up to 8 OSDs
Video Streaming	Triple
Privacy Mask	Up to 4 areas
Protocols	L2TP,IPv4,IGMP,ICMP,ARP,TCP,UDP,DHCP,PPPoE,RTP,RTSP,Qos, NTP,FTP,HTTP,SNMP,SIP
Compatible Integration	ONVIF, API



SPECIFICATION



Audio I/O	audio cable Input: impedance 35 k Ω ; amplitude 2 V [p-p] Output: impedance 600 Ω ; amplitude 2 V [p-p]
Alarm I/O	1/1
Network	1 RJ45 10M/100M Base-TX Ethernet
Video Output	1 BNC, impedance 75 Ω ; amplitude 1 V [p-p]
Reset	1 Reset Button
Power Output	DC12V Power Output With PoE
Power	12 V DC, or PoE (IEEE802.3 af) / Power consumption: max.6.6 W (PoE :max.7.2 W)
Dimensions (L x W x H)	Φ 148 x 111.3 mm (Φ 5.8" x 4.4")
Weight	0.75 kg (1.7 lb)
Working Environment	-40°C ~ +60°C (-40°F ~ 140°F), Humidity \leq 95% RH(non-condensing)
Vandal Resistant	IK10
Ingress Protection	IP66

