

# CP- UVR-3201E2

## 32 Ch. 720P HDCVI DVR



### Main Features

- Support HDCVI/Analog/IP Video input
- All channel 720P Realtime Recording
- H.264 dual-stream Video Compression
- HDMI / VGA / TV Simultaneous Video Output
- Support Multi-brand network cameras
- Support 2 SATA HDDs up to 8TB, 2 USB2.0
- Mobile Software: iCMOB, gCMOB, wCMOB
- CMS Software:KVMS, KVMS Pro



# CP- UVR-3201E2

## 32 Ch. 720P HDCVI DVR

### Feature

Processor  
 Operating System  
 Two-way Talk  
 User Interface  
 Video Input  
 Video Output  
 Video Standard  
 Compression  
 Video Resolution  
 Video Recording  
 Video Display Split  
 Privacy Masking  
 Audio Input  
 Audio Output  
 Motion Detection  
 Video Loss  
 Camera Blank  
 Alarm Input  
 Alarm Output  
 Smart Phone  
 Hard Disk  
 Trigger Events  
 Recording Mode  
 Search Mode  
 Playback  
 Backup Mode  
 Interface Ports  
 Record Interval  
 Max User Account  
 Ethernet

### Specification

Embedded processor  
 Embedded LINUX  
 Reuse audio input/output channel 1  
 GUI  
 32 channel, BNC  
 1 HDMI, 1 VGA, 1 TV  
 Analog: NTSC / PAL, HDCVI: 720P HDCVI Camera, IP: 1080P/720P/D1/CIF IP Camera  
 H.264 / G.711  
 1920×1080, 1280×1024, 1280×720, 1024×768  
 Main Stream: 720P/960H / D1(1~25/30fps), Extra Stream: CIF / QCIF(1~25/30fps)  
 1/4/8/9/16/25/36  
 4 rectangular zones (each camera)  
 1 channel, RCA  
 1 channel, RCA  
 Supports  
 Supports  
 Supports  
 N/A  
 N/A  
 iPhone, iPad, Android, Windows Phone  
 2 SATA ports, up to 8TB  
 Recording, PTZ, Tour, Video Push, Email, FTP, Spot, Buzzer & Screen tips  
 Manual, Schedule(Regular(Continuous), MD), Stop  
 Time/Date, MD & Exact search (accurate to second)  
 Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup, selection, Digital zoom  
 USB Device/Internal SATA burner/Network  
 1 HDMI, 1 VGA, 2 USB2.0, 1 RS485  
 1~60 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec  
 128 users  
 RJ-45 port (10/100M/1000M)



**CP- UVR-3201E2**  
**32 Ch. 720P HDCVI DVR**

**Feature**

Protocols

Power Supply

Power Consumption

Working Temp

Dimensions

Weight

**Specification**

HTTP, IPv4/IPv6, TCP/IP, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, SNMP, P2P, ONVIF Version 2.4 conformance

DC12V/5A

15W(Without HDD)

-10 ~+55°C / 10~90%RH / 86~106kpa

375mm × 285mm × 55mm

2.35Kg(without HDD)